

Series of Environmental Protection Electric Magnetic Stirrer



structural characteristics

PWM+PWM

Series of AC-DC-AC(PWM+PWM) frequency converter Bottom-mounted Electromagnetic stirrer Parameters Table

Model	JBDZ. 02DZ	JBDZ. 05DZ	JBDZ. 10DZ	JBDZ. 20DZ	JBDZ. 30DZ	JBDZ. 40DZ	JBDZ. 60DZ	JBDZ. 90DZ	JBDZ. 120DZ	JBDZ. 150DZ
Stir Tonnage (T)	2.2 t	5.5 t	12 t	22 t	33 t	45 t	66 t	100 t	132 t	165 t
Power(kW)	50	50	60	70	100	130	160	220	270	320
Power Factor	0.96	0.96	0.96	0.98	0.98	0.98	0.98	0.98	0.98	0.98
3		50Hz/60Hz Frequency power input parameters (three phase, frequency: 50Hz/60Hz)								
Line voltage	380V	380V	380V	380V	380V	380V				
Maximum stirring current A	75	75	90	106	150	197				
Transformer parameters (KVA)	50	50	60	70	100	130				
Number of electrical cabinets	2	2	2	3	3	3				
Cabinet size m	1×0.8×2.2	1×0.8×2.2	1×0.8×2.2	1×0.8×2.2	1×0.8×2.2	1×0.8×2.2	1×0.8×2.2	1×0.8×2.2	1×0.8×2.2	1×0.8×2.2

以上参数仅供参考，实际使用时，以技术协议为准。The above parameters are for reference only, actual use, subject to technical agreement.